

Under-Counter Pharmacy Refrigerator



HYC-118

Scope of Application:

Versatile, quiet, under-counter pharmacy refrigerator features safety lock, digital display with multiple alarms. Widely used for storage of biological products, vaccines, drugs and reagents in within pharmacy, pharma manufacture, clinical, public health and other life science laboratories.

Innovative Design

LED Display
 Ergonomic Design
 Multiple Alarms
 Lockable Design













Under-Counter Pharmacy Refrigerator

Product Advantages ()



Superior Cabinet Temperature Uniformity, Auto Defrost

There are 9 test points within the interior which ensure superior temperature uniformity



Multiple Alarm

Capable of alerting failures due to high and low temperature, sensor error, power failure, low battery, door ajar and remote alarm



Energy Efficient Hydrocarbon (HC) Refrigeration System

Optimised refrigeration system, utilising high-efficiency HC compressor significantly reduces energy consumption



LED Display

Microprocessor control, digital display and temperature adjustment with an increment of 0.1°C



Ergonomic Design

810mm cabinet height makes it easy to place under test bench, saving storage space



Greener by Design

HC refrigerants are natural non-toxic and more environmentally friendly




Lockable Design

Safety lock to prevent unauthorized access

Product Introduction









Under-Counter Pharmacy Refrigerator

Temperature Curve (





Stability Curve



Specifications



Internal Temperature
Ambient Temperature

Model			HYC-118		
Technical Data	Cabinet Type		Upright, solid door		
	Climate Class		N		
	Cooling Type		Forced air cooling		
	Defrost Mode		Auto		
	Refrigerant		HC	HC	
	Sound Level (dB(A))		41		
Performance	Temperature Range (°C)		2~8		
Control	Controller		Microprocessor		
	Display		LED		
Electrical Data	Power Supply (V/Hz)		220~240/50/60	115/60	
	Power (W)		190	190	
	Electrical Current (A)		1.4	1.4	
Dimensions	Capacity (L/Cu.Ft)		118/4.2		
	Net/Gross Weight (approx)	(kg)	41/46		
		(lbs)	90.5/1	90.5/101.5	
	Interior Dimensions (W*D*H)	(mm)	515*41	515*415*630	
		(in)	20.3*16	20.3*16.3*24.8	
	Exterior Dimensions (W*D*H)	(mm)	597*635*810		
		(in)	23.5*25.0*31.9		
	Packing Dimensions (W*D*H)	(mm)	680*690*910		
		(in)	26.8*27.2*35.8		
	Container load (20'/40'/40'H)		48/96/96		
Alarms	High/Low Temperature		Υ		
	Remote Alarm		Υ		
	Power Failure		Υ		
	Sensor Error		Υ		
	Low Battery		Υ		
	Door Ajar		Υ		
Accessories	Caster		Υ		
	Foot		Y		
	Porthole Shelves/Drawers		Y 3/1		
Certifications	CE CE		3/1 Y /		
	UL		1	Y	

*Haier Biomedical reserves the right to change products and specifications without prior notice.

Marketed by:

Bioline Technologies

Sales. Office: 404/405 Shanti dham heights, 90 feet Road
Parsik Nagar, Kalwa (W), Thane - 400 605, Maharashtra India,
Telefax: +91-22-2545 2111, +91-9594106999
Email: Info@bioline.in | Web: www.bioline.co.in
Branch: Delhi | Surat | Bangalore | Chennai | Trivandrum